




Minor

Electrical submersible drainage pump



50 Hz	N	H
Discharge connection	4"	3"
Rated power P_2 [kW]	3,7	3,7
Max. power consumption P_1 [kW]	4,4	4,4
Shaft speed [r.p.m.]	2885	2885
Rated current at 230V	13 A	13 A
Rated current at 400V	7,3 A	7,3 A
Rated current at 500V	5,4 A	5,4 A
Rated current at 1000V	2,9 A	2,9 A
Solids passage [mm]	10	10
Height [mm]	768	768
Diameter [mm]	286	286
Weight [kg]	50	50

Other voltages on request

Pump types

N: normal pressure

H: high pressure

Classification

Electrical submersible drainage pump

Protection class: IP 68

Electrical motor

Squirrel cage induction motor, insulation class: H (IEC 85)

Motor protection

Phase sequence control, phase failure guard, temperature guard with thermal contacts in the stator opening temperature 140°C (284°F) (= SMART system), air valve

Cable - SubCab

4G2,5mm², length 20 m or 14AWG/4, length 53 ft

Limitations


Max. submersion depth: 20 m (66 ft)

Max. liquid temperature: 40 °C (104 °F)


Allowed pH range: 5 - 8

Maximum liquid density: 1100 kg/m³ (68 lbs/ft³)

H (m)



P_1 (kW)



ISO 9906/A

Shaft seals

Cartridge seal: pre-assembled double mechanical seal running in an oil compartment

Material lower seal: *silicon carbide - silicon carbide*

Material upper seal: *tungsten carbide - aluminium oxide*

Bearings

Ball bearings with C3 clearance

Discharge connection

3-4" hose, ISO-G or NPT

Materials

Casted parts: *Aluminium*

Outer casing: *Stainless steel*

Motor shaft: *Stainless steel*

Impeller and suction cover: *Hard-Iron™*

Diffusers: *Nitrile rubber*

Screws and nuts: *Stainless steel*

O-rings: *Nitrile rubber*

Accessories

Level regulator

Zinc anodes

Tandem connection

Low suction collar

Pump raft

Specifications can be changed without notice